



Tech Specs - sonnen eco - Gen 3

The sonnenBatterie eco is a smart energy storage solution for your home that uses intelligent software to manage energy throughout the day – providing you with greater energy independence by supplying backup power and enabling you to use your solar power at night.

	eco 5 ¹	eco 7.5	eco 10 ¹	eco 12.5	eco 15	eco 17.5	eco 20
Total capacity (@ 90% DOD)²	5 kWh	7.5 kWh	10 kWh	12.5 kWh	15 kWh	17.5 kWh	20 kWh
Nominal power rating (off-grid output at 25 deg C)	3 kW	4 kW	8 kW	8 kW	8 kW	8 kW	8 kW
Nominal power rating (grid-tied output at 25 deg C)	3 kW	3.6 kW	7 kW	7 kW	7 kW	7 kW	7 kW
Weight (approximate)	331 lbs	381 lbs	474 lbs	585 lbs	635 lbs	685 lbs	735 lbs
Dimensions W"/H"/D" (approximate)	26/57/16				26/84/16		

Off-grid specification	eco 5 ¹	eco 7.5	eco 10 ¹	eco 12.5	eco 15	eco 17.5	eco 20
Continuous AC output current	12.5 A	16.67 A			33.3 A		
Max power	100 ms - 8.5 KVA 5 s - 6 KVA 30 m - 4.5 KVA				100 ms - 17 KVA 5 s - 12 KVA 30 m - 9 KVA		
Max AC current (charge/discharge)	1 ms - 50A 100 ms - 35.35 A 5 s - 25 A 30 m - 18.75 A				1 ms - 100A 100 ms - 70.7 A 5 s - 50 A 30 m - 37.5 A		

General specification

Grid integration	AC coupled
Applications	Self-consumption Backup power Time-of-use
Transfer switch	Automatic, integrated
Usable capacity	2.25 kWh per battery module, up to 8 modules
Listed and recognized components	System certified – UL9540; Battery modules – UL1973; Inverter – UL1741; Transfer switch – UL1008; AC Breaker – UL489
Warranty	10 year or 10,000 cycle system warranty – includes inverter, battery modules, cabinet and components ³
Inverter efficiency	92.5% CEC weighted, 95.0% peak
Roundtrip efficiency % (Grid<>Battery)	>= 86%
Temperature range	41 °F - 113 °F
Ventilation	Forced Air
Comm. ports	Ethernet
Communication protocols / Control	SunSpec Alliance / API available to select partners
Passthrough current rating	200 amps (Switching and overcurrent protection)
EMC / EMI protection	FCC Part 15B

Battery specification

DC battery input voltage	44.5–53.5 VDC
Max charge current	50 A per module
Cell discharge	2.5kWh with 90% DoD
Overcharge protection	MOSFET & Fuse protection

AC specification

AC grid voltage	120/240 VAC (Split phase)
Nominal AC input current (grid-tied operation)	
eco 5	12 amps
eco 7.5	15 amps
eco 10-20	29 amps
Nominal frequency	60 Hz
Adjustable frequency range	+/- 0.7 Hz from nominal
Metering capability	Power meter for load and PV production (not revenue grade)
Tare losses (W)	60 watts
Transient protection	IEEE C62.41 Class B

Measurements



-For Puerto Rico, the sonnen eco comes standard with the front screen.

sonnen Inc.

2048 Weems Road, Suite C, Tucker, GA 30084
(310) 853-2404

We reserve the right to make technical changes. The values, outputs, other technical data, images, and diagrams in this prospectus and in data sheets, advertisements, and other promotional documents are approximate guidelines in all cases where they have not been identified as binding.

1 The eco Gen 3.1 is available in two base models, the eco 5 and the eco 10, with the ability to add battery modules to increase capacity.

2 eco Gen 3.1 battery modules are 2.5kWh in total capacity and at a 90% DoD represent 2.25kWh of usable capacity per module.

3 Please observe our applicable warranty conditions.